

Titan Trap™ Vacuum Cold Trap

Applications

- ▶ Protection of oil-sealed vacuum pumps
- ▶ Gel drying
- ▶ Evaporators
- ▶ Dryers
- ▶ Dehydration of gas streams

Benefits

- ▶ Increases surface area available for trapping
- ▶ Resists corrosion
- ▶ Automates process including vacuum pump activation and defrost/shut-down routine
- ▶ Conserves space
- ▶ Provides visibility and corrosion resistance



Call **800-824-0400**
or visit www.ftssystems.com

Maximum efficiency for vacuum trapping of corrosive vapors to -100°C



TT4105

Features at a Glance

- Helical-wound, ultra-low temperature refrigerated titanium coil
- Titanium coil and Teflon®-coated stainless steel chamber
- Corrosive resistant drain
- Optional microprocessor
- Ultra-compact units
- Safety-coated glass dome top
- Accommodates vacuum pump flow rates up to 250 liters per minute (9 scfm)

Model Specifications¹

	TT455	TT855	TT4105	TT8105
Maximum Low Temperature °C	-50	-50	-100	-100
Chamber Volume (liters)	4	8	4	8
Trapping Rate (liters/24 hours)	3	5	3	5
Compressor	1/4 hp	1/3 hp	Two @ 1/4 hp	Two @ 1/4 hp
Controls standard: option:	On/Off Microprocessor	On/Off Microprocessor	On/Off Microprocessor	On/Off Microprocessor
Indication °C standard: option:	1 0.1 with MP	1 0.1 with MP	1 0.1 with MP	1 0.1 with MP
Dimensions W x D x H inches cm	15.5 x 24 x 13 ² 39 x 61 x 33	15.5 x 24 x 13 ² 39 x 61 x 33	19 x 24 x 13 ² 48 x 61 x 33	19 x 24 x 13 ² 48 x 61 x 33
Weight lbs/kg	55/25	55/25	85/39	85/39
Electrical ³	120V/60 Hz/14A	120V/60 Hz/14A	120V/60 Hz/17A	120V/60 Hz/17A

1. Titan traps include safety-coated glass top.
2. Allow an extra 6" in height to include the glass top.
3. 220V/50 Hz also available. Decreases heat removal by 17%.



Committed to Product Excellence...and Continuous Support

SP Industries

PO Box 158 3538 Main Street Stone Ridge, NY 12484 USA
800.824.0400 Phone : 845.687.0071 Fax: 845.687.7481 www.ftssystem.com

VirTis FTS Hull Wilmad|LabGlass Hotpack Genevac

SP Industries Corporate Headquarters:

935 Mearns Road Warminster, PA 18974 USA 800.523.2327 Phone: 215.672.7800 Fax: 215.672.7807 www.SPindustries.com